

HIXCO



SBE561
1/2" Hammer Drill

Model #	SBE561
Order #	601160420
Variospeed (V) electronics	●
Maximum speed controlled by adjusting dial	●
Reversing switch	●
Rubber coated comfort handle	●
Chuck	1/2" Geared
Maximum tightening torque	40 inch lbs.
	Inquire about 220V availability
Capacity	
- in concrete	1/2"
- in mild steel	3/8"
- in softwood	3/4"
No-load speed (RPM)	0-2800
No-load blows per minute (BPM)	0-50000
Amps	4.5
Rated input watts	560
Chuck capacity	1/2"
Spindle thread	1/2 x 20 UNF
Tool weight	5.3 lbs.
Shipping weight	7 lbs.
Length	10 3/4"
Carrying case	344452990 (standard)
Standard Equipment:	1/2" chuck (636614000) Side handle (631052000) Depth gauge (341511630) Chuck key (635167000)

Optional Equipment:

630828000 Dust extraction kit

For bit diameters up to 3/4". Precise depth stop. 15' hose allows wide area use. Fits SBE561, SBE710, SBE751, SBE1100.

(See page 33 for straight shank hammer drill bits)

HIXCO



SBE710
1/2" Hammer Drill



SBE751
1/2" Hammer Drill



SBE1100 Plus
1/2" Hammer Drill

Model #	SBE710	SBE751	SBE1100 Plus
Order #	600862620	600863620	600867620
Variospeed (V) electronics	●	●	
Vario tacho constamatic (VTC) electronics			●
LongLife motor	●	●	●
Electronic winding-temperature monitor			●
Aluminum die-cast gear housing	●	●	●
Safety non-slip Side handle	●	●	●
2-speed gear-box	●	●	●
Electronic soft start feature			●
Max. speed controlled by adjusting dial			●
Current interruption protection			●
Maintenance reminder light			●
Swivel cord connection	●	●	●
Reversing switch	●	●	●
Chuck	1/2" Geared	1/2" Geared	1/2" Keyless
Metabo slip clutch	●	●	●
Auto-stop carbon brushes	●	●	●
Winding protection grid	●	●	●
Maximum tightening torque	248 inch lbs.	265 inch lbs.	389 inch lbs.
	Inquire about 220V availability	Inquire about 220V availability	Inquire about 220V availability
Rubber coated handle	●	●	●
Capacity			
- in concrete	3/4"	3/4"	3/4"
- in mild steel	1/2"	1/2"	5/8"
- in softwood	1 9/16"	1 9/16"	1 9/16"
No-load speed (RPM)	0-1000/0-3100	0-1000/0-3100	0-900/0-2800
No-load blows per minute (BPM)	0-59,000	0-59,000	0-53,000
Amps	5.8	6.5	9.6
Rated input watts	710	750	1100
Chuck capacity	1/2"	1/2"	1/2"
Spindle thread	1/2 x 20 UNF	1/2 x 20 UNF	1/2 x 20 UNF
Tool weight	6.8 lbs.	7.0 lbs.	7.4 lbs.
Shipping weight	11.5 lbs.	11.7 lbs.	12.1 lbs.
Length	14 1/2"	14 1/2"	14 1/2"
Carrying case	344454110 (standard)	344454110 (standard)	344454110 (standard)
Standard Equipment:	1/2" chuck (635250000) Side handle (314001030) Depth gauge (341511630) Chuck key (635167000)	1/2" chuck (635250000) Side handle (314001030) Depth gauge (341511630) Chuck key (635167000)	1/2" chuck (636226000) Side handle (314001020) Depth gauge (341511630)
Optional Equipment:	Dust extraction kit (631600000)	Dust extraction kit (631600000)	Dust extraction kit (631600000)