

# HIXCO



**WE14-125 Inox Plus**  
4 1/2" Angle Grinder

<b>Model #</b>	<b>WE14-125 Inox Plus</b>
<b>Order #</b>	<b>602131420</b>
Vario tacho constamatic (VTC) electronics	●
LongLife motor	●
Quick wheel change system	●
Switch with lock on capability	●
Current interruption protection	●
Spindle lock	●
Low profile aluminum die-cast gear housing	●
Variable speed dial	●
Burst-proof guard w/ 7 stops	●
Anti-vibration Side handle	●
Electronic winding temperature monitor with LED display	●
Metabo slip clutch	●
Auto-stop carbon brushes	●
Winding protection grid	●
Electronic soft start feature	●
Electronic speed stabilization	●
Maximum torque	37.2 inch lbs.
	Inquire about 220V availability
Maximum wheel diameter	5"
No-load speed (RPM)	2000-7000
Amps	12.2
Rated input watts	1400
Arbor size	7/8"
Spindle thread	5/8"-11
Tool weight	6.2 lbs.
Shipping weight	7.2 lbs.
Length	12.25"
Carrying case	344454180 (optional)

<b>Standard Equipment:</b>	Side handle (314000970) Wheel guard (339203010) Inner flange (341031290) Outer nut (316031310)
----------------------------	---



**SE12-115**  
Burnisher

NEW

<b>Model #</b>	<b>SE12-115</b>
<b>Order #</b>	<b>602115620</b>
<b>Order # "Bare" Tool w/case</b>	<b>US602115110</b>
Maximum size	4.5" dia. x 4" length
Double insulated	●
Vario tacho constamatic (VTC) electronics	●
LongLife motor	●
Quick wheel change system	●
Spindle lock	●
Winding protection grid	●
High performance spiral bevel gears	●
Variable speed controlled by adjusting dial	●
Auto-stop carbon brushes	●
Maximum torque	98 inch lbs.
	Inquire about 220V availability
No-load speed (RPM)	900-2800
Amps	10.0
Rated input watts	1200
Spindle thread	5/8"-11
Tool weight	6.25 lbs.
Shipping weight	23.5 lbs.
Length	13.5"
Carrying case	344453120 (standard)

<b>Standard Equipment:</b>	Case (344453120) 3 - P80 Sanding belt (623474000) 2 - 2" x 4" P180 Interleaved (623528000) 1 - Expansion roll for grinding and polishing sleeves (623470000) 1 - Set of spacer rings (623511000) 1 - 4" x 4" P280 Non-woven nylon wheel (623514000) 1 - P80 Flap wheel (623479000) 1 - Spindle extension kit (US90357014)
----------------------------	--

<b>Optional Equipment:</b>	2" Spindle (626413000)
----------------------------	------------------------

# HIXCO



**RBE12-180**  
Pipe / Tube Sander



**KNSE12-150**  
Fillet Weld Grinder

Model #	RBE12-180	KNSE12-150
Order #	602132620	602133620
Vario tacho constamatic (VTC) electronics	●	●
LongLife motor	●	●
Switch with lock on capability	●	●
Current interruption protection	●	●
Spindle lock	●	●
Low profile aluminum die-cast gear housing	●	●
Variable speed dial	●	●
Adjustable guard		●
Ergonomic Side handle	●	●
Electronic winding temperature monitor with LED display	●	●
Auto-stop carbon brushes	●	●
Winding protection grid	●	●
Electronic soft start feature	●	●
Electronic speed stabilization	●	●
	Inquire about 220V availability	Inquire about 220V availability
Maximum pipe or disc diameter	7"	6"
Dimensions of grinding belt	1-1/2" x 30"	n/a
Wrap angle (maximum)	270°	n/a
No-load speed	521-1,673 ft./min	1,300-4,000 RPM
Amps	10.0	10.0
Rated input watts	1200	1200
Arbor size	n/a	1"
Spindle thread	n/a	5/8"-11
Tool weight	9.1 lbs.	7.75 lbs.
Shipping weight	29.3 lbs.	20.1 lbs.
Length	20 1/4"	22 1/2"
Carrying case	344453970 (standard)	344453990 (standard)
Standard Equipment:	Side handle (316046590) 10 Zirconia alumina sanding belts P80 (626306000)	Side handle (316046590) Wheel guard (339203590) Flange set (316047400) Hex wrench (344161510) Spanner wrench (623934000) Fleece compact disc (6" x 1/4" x 1", medium) (626402000)

# HIXCO



**Band File**  
BFE9-90



Shown with optional backing pad (655143000)

**PE12-175**  
Variable Speed High Torque Mini Polisher

<b>Model #</b>	<b>BFE9-90</b>
<b>Order #</b>	<b>602134620</b>
Vario constamatic (VC) electronics	●
LongLife motor	●
Quick belt change system	●
Switch with lock on capability	●
Spindle lock	●
Low profile aluminum die-cast gear housing	●
Ergonomic Side handle	●
Metabo slip clutch	●
Auto-stop carbon brushes	●
Winding protection grid	●
Maximum torque	22 inch lbs.
	Inquire about 220V availability
Sanding belt size	1/4", 1/2", 3/4" x 18"
No-load belt speed	750-1770
Amps	8.5
Rated input watts	900
Useful length of grinding belt arm	3-1/2"
Tool weight	5.5 lbs.
Shipping weight	17.4 lbs.
Length	18 1/8"
Carrying case	344453980 (standard)

**Standard Equipment:** Side handle (316046590)  
10 Zirconia alumina sanding belts (P120, 1/4" in width) (626347000)  
Grinding arm - for belt widths of 1/4" and 1/2" (626379000)

<b>Model #</b>	<b>PE12-175</b>
<b>Order #</b>	<b>602175420</b>
Maximum pad diameter	7"
Double insulated	●
Vario tacho constamatic (VTC) electronics	●
LongLife motor	●
Spindle lock	●
Winding protection grid	●
High performance spiral bevel gears	●
Variable speed controlled by adjusting dial	●
Auto-stop carbon brushes	●
Maximum torque	124 inch lbs.
	Inquire about 220V availability
No-load speed (RPM)	700-2200
Amps	10.0
Rated input watts	1200
Spindle thread	5/8"-11
Tool weight	5.9 lbs.
Shipping weight	7.6 lbs.
Length	14 1/4"
Carrying case	631382000 (optional)

**Standard Equipment:** Side handle (314000540)  
Hand guard (630327000)  
Spindle extension (341513050)

